

| | | |
|---------------------------------------|---|------------------------------|
| Model Number 039225-50101/B | ROTARY TORQUE, W/ENCODER AND AUTO ID | Revision: NR ECN #: 47364 |
|---------------------------------------|---|------------------------------|

| | <u>ENGLISH</u> | <u>SI</u> | |
|---|-----------------------------|-----------------------------|--------|
| Performance | | | |
| Measurement Range(Full Scale Capacity) | 100 lbf-in | 11.3 Nm | |
| Sensitivity(output at rated capacity) | 2.0 mV/V | 2.0 mV/V | [7] |
| Non-Linearity | ≤ 0.25 % FS | ≤ 0.25 % FS | [2] |
| Hysteresis | ≤ 0.25 % FS | ≤ 0.25 % FS | [2] |
| Non-Repeatability | ≤ 0.05 % FS | ≤ 0.05 % FS | [2] |
| Interchangeability | ≤ 0.30 % FS | ≤ 0.30 % FS | [8][2] |
| Environmental | | | |
| Overload Limit | 150 lbf-in | 16.9 Nm | |
| Temperature Range(Operating) | 0 to +200 °F | -18 to +93 °C | |
| Temperature Range(Compensated) | +70 to +150 °F | +21 to +66 °C | |
| Temperature Effect on Output(Maximum) | ± 0.002 %Reading/°F | ± 0.0018 %Reading/°C | [6] |
| Temperature Effect on Zero Balance(Maximum) | ± 0.002 %FS/°F | ± 0.0018 %FS/°C | [6] |
| Electrical | | | |
| Bridge Resistance | 350 Ohm | 350 Ohm | |
| Excitation Voltage | 10 VDC | 10 VDC | [1] |
| Insulation Resistance | ≥ 5 GOhm | ≥ 5 GOhm | |
| Zero Balance | ≤ 2 % FS | ≤ 2 % FS | [2] |
| Counts Per Revolution | 1472 | 1472 | [3] |
| Resolution w/ Quadrature | 1/4 ° | 1/4 ° | [3] |
| Output Voltage | High 5V to Low 0.5V | High 5V to Low 0.5V | [3] |
| Power Required(maximum) | 5 VDC @ 120mA | 5 VDC @ 120mA | [3] |
| Magnetic Encoder(Poles) | 360 | 360 | |
| Magnetic Encoder(Output) | See Note | See Note | [4][3] |
| Shunt Calibration | ≤ 0.25 % FS | ≤ 0.25 % FS | [5][2] |
| Auto ID | TTL Proprietary | TTL Proprietary | |
| Physical | | | |
| Size (Shaft Length x Housing Length x Housing Height) | 3.23 in x 2.30 in x 2.00 in | 82.0 mm x 58.4 mm x 50.8 mm | [9] |
| Weight | .75 lb | 340 gm | |
| Mounting | 1/4 inch Sq Drive | 6.35 mm Sq Drive | [10] |
| Sensing Element | Strain Gage | Strain Gage | |
| Housing Material | Aluminum | Aluminum | |
| Shaft Material | Steel | Steel | |
| Electrical Connector | PT02H-12-10P | PT02H-12-10P | |
| Maximum Speed | 5000 RPM | 5000 RPM | |

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

NOTES:

[1] Calibrated at 10 VDC, usable 5 to 20 VDC or VAC RMS.
 [2] FS - Full Scale.
 [3] Magnetic Encoder Specifications.
 [4] A-B Track 90° Phase Difference, Flat Over Operating Speed
 [5] Matched with 43.575 kOhm Precision Resistor.
 [6] Over compensated temperature range.
 [7] Matched to ±0.25% F.S.
 [8] Matched for mV/V and shunt calibration.
 [9] See Outline Drawing 45187 for Complete Dimensions
 [10] Per ANSI B107.4 Specifications
 [11] See PCB Declaration of Conformance PS119 for details.

SUPPLIED ACCESSORIES:
 Model 7122R-04352A PRECISION CAL RESISTOR 43.575 kOhm

OPTIONAL ACCESSORIES:
 Model 080920-01000 Model 920 Portable Digital Peak Meter for torque, torque-angle or load measurement; Click-Wrench calc feature, w/battery charger, instruction manual & shoulder strap
 Model 080962-01000 MODEL 962 DATA RECORDER
 Model 097000-34445 INTERCONNECT CABLE
 Model 4242R-000630 MATING CONNECTOR PT06A-12-10S(SR)

| | | | | |
|------------------|------------------|------------------|------------------|--------------|
| Entered: LK | Engineer: PE | Sales: DM | Approved: JSD | Spec Number: |
| Date: 10/31/2017 | Date: 10/31/2017 | Date: 10/31/2017 | Date: 10/31/2017 | 68201 |



All specifications are at room temperature unless otherwise specified.
 In the interest of constant product improvement, we reserve the right to change specifications without notice.



PCB Load & Torque
 A Division of PCB Piezotronics
 24350 Indopex Circle
 Farmington Hills, MI 48335
 UNITED STATES
 Phone: 866-684-7107
 E-Mail: LTSales@pcb.com
 Web site: www.pcb.com/LoadAndTorque