

	ENGLISH	SI	
Performance			
Measurement Range (for ±5V output)	1 kpsi	6900 kPa	
Useful Overrange (for ± 10V output)	2 kpsi	13790 kPa	[2]
Sensitivity (±10 %)	5.0 mV/psi	0.7 mV/kPa	
Maximum Pressure (static)	10 kpsi	69000 kPa	
Resolution	20 mpsi	0.14 kPa	[1]
Resonant Frequency	≥500 kHz	≥500 kHz	
Rise Time (Reflected)	≤1.0 μ sec	≤1.0 μ sec	
Low Frequency Response (-5 %)	0.005 Hz	0.005 Hz	
Non-Linearity	≤1.0 % FS	≤1.0 % FS	[3]
Environmental			
Acceleration Sensitivity	≤0.002 psi/g	≤0.0014 kPa/(m/s ²)	
Temperature Range (Operating)	-100 to +275 °F	-73 to +135 °C	
Temperature Coefficient of Sensitivity	≤0.03 %/°F	≤0.054 %/°C	[1]
Maximum Flash Temperature	3000 °F	1650 °C	
Maximum Shock	20000 g pk	196140 m/s ² pk	
Electrical			
Output Polarity (Positive Pressure)	Positive	Positive	
Discharge Time Constant (at room temp)	≥100 sec	≥100 sec	
Excitation Voltage	20 to 30 VDC	20 to 30 VDC	
Constant Current Excitation	2 to 20 mA	2 to 20 mA	
Output Impedance	<100 Ohm	<100 Ohm	
Output Bias Voltage	8 to 14 VDC	8 to 14 VDC	
Electrical Isolation	10 ⁸ Ohm	10 ⁸ Ohm	
Physical			
Sensing Geometry	Compression	Compression	
Sensing Element	Quartz	Quartz	
Housing Material	Stainless Steel	Stainless Steel	
Diaphragm	Invar	Invar	
Sealing	Welded Hermetic	Welded Hermetic	
Electrical Connector	10-32 Coaxial Jack	10-32 Coaxial Jack	
Weight	0.41 oz	11.6 gm	

Optional Versions (Optional versions have identical specifications and accessories as listed for standard model except where noted below. More than one option maybe used.)

- CA** - Ablative Coating
- H** - Hermetic Seal

Sealing	Welded Hermetic	Welded Hermetic
---------	-----------------	-----------------
- M** - Metric Mount

Supplied Accessory: Model 065A40 Seal ring, 0.435" OD x 0.397" ID x 0.030" thk, brass (for Models 061A07 and 061A10 thread adaptors) replaces Model 065A03
- N** - Negative Output Polarity
- S** - Stainless Steel Diaphragm

Diaphragm	316L Stainless Steel	316L Stainless Steel
-----------	----------------------	----------------------
- W** - Water Resistant Cable

Notes

- [1] Typical.
- [2] For +10 volt output, minimum 24 VDC supply voltage required. Negative 10 volt output may be limited by output bias.
- [3] Zero-based, least-squares, straight line method.
- [4] See PCB Declaration of Conformance PS023 for details.

Supplied Accessories
065A03 Seal ring 0.435" OD x 0.377" ID x 0.030" thk brass (3)



All specifications are at room temperature unless otherwise specified.
In the interest of constant product improvement, we reserve the right to change specifications without notice.
ICP® is a registered trademark of PCB group, Inc.

Entered: DMW	Engineer: NJL	Sales: RWM	Approved: ECB	Spec Number:
Date: 12/22/2010	Date: 12/22/2010	Date: 12/22/2010	Date: 12/22/2010	40730

	3425 Walden Avenue Depew, NY 14043 UNITED STATES Phone: 800-828-8840 Fax: 716-684-0987 E-mail: info@pcb.com Web site: www.pcb.com
--	---