

	ENGLISH	SI	
Performance			
Measurement Range (for ±5V output)	500 psi	3447 kPa	[1]
Measurement Range (for ±10V output)	1 kpsi	6895 kpsi	
Sensitivity (±15 %)	10 mV/psi	1.45 mV/kPa	
Maximum Pressure	5 kpsi	34474 kPa	
Resolution	1 mpsi	.007 kPa	[2]
Resonant Frequency	≥400 kHz	≥400 kHz	
Rise Time (Incident)	≤6.5 μ sec	≤6.5 μ sec	
Non-Linearity	≤1.0 % FS	≤1.0 % FS	[3]
Environmental			
Temperature Range (Operating)	-100 to +275 °F	-73 to +135 °C	
Temperature Coefficient of Sensitivity	≤0.05 %/°F	≤0.090 %/°C	
Electrical			
Discharge Time Constant (at room temp)	≥0.2 sec	≥0.2 sec	
Excitation Voltage	20 to 30 VDC	20 to 30 VDC	
Constant Current Excitation	2 to 20 mA	2 to 20 mA	
Output Impedance	≤100 Ohm	≤100 Ohm	
Output Bias Voltage	8 to 14 VDC	8 to 14 VDC	
Physical			
Sensing Geometry	Compression	Compression	
Sensing Element	Quartz	Quartz	
Housing Material	Aluminum	Aluminum	
Diaphragm	Invar	Invar	
Sealing	Epoxy	Epoxy	
Electrical Connector	BNC Jack	BNC Jack	
Weight	12.4 oz	352 gm	[2]

Optional Versions (Optional versions have identical specifications and accessories as listed for standard model except where noted below. More than one option maybe used.)

- Notes**
- [1] For +10 volt output, minimum 26 VDC supply voltage required. Negative 10 volt output may be limited by output bias.
 - [2] Typical.
 - [3] Zero-based, least-squares, straight line method.
 - [4] See PCB Declaration of Conformance PS023 for details.

Supplied Accessories
 PCS-6 Calibration of Series 134, 137, and 138 (1)



All specifications are at room temperature unless otherwise specified.
 In the interest of constant product improvement, we reserve the right to change specifications without notice.
 ICP® is a registered trademark of PCB group, Inc.

Entered: AP	Engineer: JDK	Sales: RWM	Approved: BAM	Spec Number:
Date: 08/14/2013	Date: 08/14/2013	Date: 08/14/2013	Date: 08/14/2013	55318

3425 Walden Avenue
 Depew, NY 14043
 UNITED STATES
 Phone: 800-828-8840
 Fax: 716-684-0987
 E-mail: info@pcb.com
 Web site: www.pcb.com